



AIMSHOP.COM



• LAP TIMERS • LOGGERS • CAMERAS • DASHES • SENSORS • AND MORE

SHOP NOW

AiM Infotech

Peugeot Funyo SP05 ECU

Release 1.00



ECU



VISIT SUPPORT CENTER

SOFTWARE DOWNLOADS

FIRMWARE UPDATES

PRODUCT DOCUMENTATION



1 Supported models and years

This tutorial explains how to connect Peugeot Prototype to AiM devices. Supported model and year is:

- Peugeot Funyo SP05 2015

2 Connection to AiM devices

Peugeot Funyo SP05 2015 is equipped with a Peugeot 1.6 Ir turbo engine. The vehicle ECU features a bus communication protocol based on CAN that can be reached on a plastic box placed behind the steering wheel and shown here below. As you can see there are four free wires coming from the plastic box, to be used for CAN connection. Bottom of the image is connection table.



Wire colour	Pin function	AiM cable
Red	CAN High	CAN+
Grey	CAN Low	CAN-

Please note: if your AiM device is SoloDL, EVO4 or ECU Bridge CAN/RS232 version with free wires (X90BGGPI2RMA) it is necessary to remove the 120 Ohm resistor you find between CAN High and CAN Low in the device cable

2

AiM device configuration

Before connecting the device to the ECU set it up using AiM Race Studio software the parameters to select in the device configuration are:

- ECU manufacturer: "Peugeot"
- ECU Model: "Funyo_sp05"

3

Available channels

Channels received by AiM devices connected to "Peugeot" "Funyo_sp05" protocol are:

ID	CHANNEL NAME	FUNCTION
ECU_1	ECU_RPM	RPM
ECU_2	ECU_TORQUE	Torque
ECU_3	ECU_PPS	Pedal position sensor
ECU_4	ECU_REQ_CHARGE	Requested charge
ECU_5	ECU_ENG_TEMP	Engine temperature
ECU_6	ECU_OIL_TEMP	Oil temperature